
# **Product MSDS**

### 6' & 4' TireSwing & Spinner Wear Mat

**Product MSDS Information 2012** 



## "A Safer Tomorrow, Begins Today!"

Designed specifically for use under playground equipment, high traffic areas, limit the loss or displacement of loose fill in kick out areas on the playground. Beveled TireSwing and Spinner Wear Mats offers a unique combination of shock attenuation, low maintenance, long wear, and accessibility.

#### 1.) COMPANY IDENTIFICATION

Pierceton Rubber Products, Inc. 3076 South 900 East Pierceton, IN 46562 800-714-1302 (Weekdays 8:00 AM -4:00 PM Eastern Time)

#### 2.) PRODUCT DESCRIPTION

Beveled TireSwing Wear Mat **Beveled Spinner Wear Mat** 

#### 3.) PRODUCT SPECIFICATION

- 1.) Product #R20OCT7272 Size: 6' (+/-1/4") Weight: 285 Lbs.
- 2.) Product #R20OCT4848 Size: 4' (+/-1/4") Weight: 100 Lbs.
- 3.) Product #R20BS7272 Size: 6' (+/-1/4") Weight: 285 Lbs.
- 4.) Product #R20BS4848 Size: 4' (+/-1/4") Weight: 100 Lbs.

#### 4.) BINDING PRODUCT

Urethane

#### 5.) BASE MATERIAL

Recycled Vulcanized Tire Rubber

#### 6.) HAZARDS IDENTIFICATION

(with in finished product) The burning of dry polyurethane or (cured) may result in the potential of toxic vapors or gases such as oxides of carbon. The burning of tire rubber will result in emissions of black smoke and may release toxic vapors or gases into the atmosphere.

#### 7.) FIRE FIGHTING MEASURES

Flash Point and Method: Not Determined potential of toxic vapors or gases such as Autoignition Temperature: Not Known and may release toxic vapors or gases Extinguishing Media: Water, CO 2, or dry chemical for dried film. Special Fire Fighting Procedures: Use pre-described extingishing media and wear self-contained breathing apparatus approved by NIOSH.

